












## TECHNICAL INFORMATION / TEKNISK INFORMATION



# BERGO BRIQ

Material:		ISO2076	Environmentally friendly recyclable /Umweltfreundliches recycelbares UV-stabilized polypropylene. /UV-stabiliserad polypropen.
Size of tile: /Plattans storlek:		EN427	377,2 x 377,2 mm. 1 m <sup>2</sup> / box = 7 tiles. 5 m <sup>2</sup> / box = 35 tiles.
Thickness of tile: /Plattans tjocklek:		EN428	10,1 mm.
Weight: /Vikt:		EN430	1 tile: 0,366 kg. 1 m <sup>2</sup> : 2,272 kg (Consumer pack). 5 m <sup>2</sup> : 13,4 kg (Maxi-pack).
Point load: /Punktbelastning:		QUALIFIED TEST BY BERGO	250 ton / 1 m <sup>2</sup> = 2500 kg/dm <sup>2</sup>
Light fastness: /Ljusbeständighet:		EN 14836 (>3) ISO 105-B02 (1-8)	4-5 7-8
Weather Fastness /UV- Floorida test (1-5):		ASTM D1435 ASTM G154 Cycle A	4/5
Slip resistance: /Halkmotstånd:		SSEN-13893	>0,4
Impact resistance: /Slagtålighet:		ISO179/1eA ASTM D746	+23 °C = 20 kJ/m <sup>2</sup> / -20 °C = 5 kJ/m <sup>2</sup> C15 kJ/m <sup>2</sup>
Fire category /Brandklassning:		EN ISO 11925-2	E <sub>fl</sub>
CE certification:		EN 14041	0402-CPD-P605080A

Packaging:	Quantity / packaging unit:	Quantity / pallet:	Size of pallet:
Consumer-pack	1 m <sup>2</sup> = 7 tiles	1 pallet = 90 cartons = 90 m <sup>2</sup>	1,20 x 0,80 x 1,23 m = 1,18 m <sup>3</sup> , 272 kg gross weight
Maxi-pack	5 m <sup>2</sup> = 35 tiles	1 pallet = 36 cartons = 180 m <sup>2</sup>	1,20 x 0,80 x 2,41 m = 2,31 m <sup>3</sup> , 499 kg gross weight

